



Image is for illustrative purposes only. Actual product may vary.

Nominal data

Model	BL-F97A-EC-00	
Motor model	MEC3E-59-40-00	

Phase		1~
Nominal Voltage	VAC	230
Nominal voltage range	VAC	184~276
Frequency	Hz	50/60

Speed	RPM	3200
Power consumption	W	37
Current draw	A	0.35
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	+60

Power and current values represent maximum ratings; speed values are specified at maximum efficiency point.

Data according to Commission Regulation (EU) 2024/1834

General parameters		
Measurement category		
Overall efficiency, ns	%	
Minimum efficiency, n	%	

Working point		
Power	W	
Flow rate	m ³ /h	
Pressure (Ps)	Pa	

Technical Data

Weight	0.57 kg
Impeller size	97 mm
Impeller material	Galvanized steel
Number of blades	34
Direction of rotation	Clockwise, seen on rotor
Motor size	59
Bearing type	Ball bearings
Insulation class	B
Degree of protection	IP55
Motor protection	Self-resetting TOP wired internally
Operation mode	Continuous duty (S1)
Installation position	Any
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Cable length	1250 ±20 mm
Technical features	<ul style="list-style-type: none">- Control Input 0-10 VDC / PWM- Locked Rotor Protection- Thermal Protection- Excessive Voltage Protection- Less Voltage Protection- Overcurrent Protection- Soft Start- Output 10 VDC, Max. 10 mA
Conformity with standards	<ul style="list-style-type: none">- Safety standards: EN 60335-1, EN 60335-2-80- Material compliance: RoHS, REACH- Quality certification: ISO 9001
Warranty period	2 years / 40 000 motor hours

Connection diagram

	Designation	Color	Function / assignment
Line 1 - Power connections	PE	Green/Yellow	Protective Earth
	L	Brown	Power supply, live wire see nameplate for voltage range
	N	Blue	Power supply, neutral wire see nameplate for voltage range

	Designation	Color	Purpose / Function
Line 2 - Control connections	+10V DC	Red	Fixed voltage output 10 VDC ±5%, max. 10mA, power supply for external devices (e.g. potentiometers), SELV
	Speed Control	Yellow	0-10V/PWM (max. amplitude of PWM 10V) control input, SELV
	Signal Feedback	White	Tach output, 2 pulse per revolution (pulses can be customized, or changed to RD signal), SELV
	GND	Blue	Reference ground for control interface, SELV

CAUTION: incorrect connection may lead to product malfunction or permanent damage.

