



Image is for illustrative purposes only. Actual product may vary.

### Nominal data

<b>Model</b>	<b>BC-B190B-EC-16</b>	
<b>Motor model</b>	<b>MEC3C-72-174-03</b>	

<b>Phase</b>		1~
<b>Nominal Voltage</b>	VAC	120
<b>Nominal voltage range</b>	VAC	
<b>Frequency</b>	Hz	50/60

<b>Speed</b>	RPM	3700
<b>Power consumption</b>	W	119
<b>Current draw</b>	A	1.6
<b>Min. ambient temperature</b>	°C	-25
<b>Max. ambient temperature</b>	°C	+50

Power and current values represent maximum ratings; speed values are specified at maximum efficiency point.

### Data according to Commission Regulation (EU) 2024/1834

General parameters		
<b>Measurement category</b>		
<b>Overall efficiency, ns</b>	%	
<b>Minimum efficiency, n</b>	%	

Working point		
<b>Power</b>	W	
<b>Flow rate</b>	m <sup>3</sup> /h	
<b>Pressure (Ps)</b>	Pa	

## Technical Data

<b>Weight</b>	1.6 kg
<b>Impeller size</b>	190 mm
<b>Impeller material</b>	PA plastic + 30% glass fiber
<b>Number of blades</b>	7
<b>Direction of rotation</b>	Clockwise, seen on rotor
<b>Motor size</b>	72
<b>Bearing type</b>	Ball bearings
<b>Insulation class</b>	B
<b>Degree of protection</b>	IP54
<b>Motor protection</b>	Self-resetting TOP wired internally
<b>Operation mode</b>	Continuous duty (S1)
<b>Installation position</b>	Any
<b>Min. permitted ambient temp. for motor (transport/storage)</b>	-40 °C
<b>Max. permitted ambient temp. for motor (transport/storage)</b>	+80 °C
<b>Cable length</b>	500 ±20 mm
<b>Technical features</b>	<ul style="list-style-type: none"> <li>- Soft Start</li> <li>- Overcurrent Protection</li> <li>- Less Voltage Protection</li> <li>- Excessive Voltage Protection</li> <li>- Thermal Protection</li> <li>- Locked Rotor Protection</li> <li>- Control Input 0-10 VDC / PWM</li> <li>- Output 10 VDC, Max. 10 mA</li> </ul>
<b>Conformity with standards</b>	<ul style="list-style-type: none"> <li>- Quality certification: ISO 9001</li> <li>- Material compliance: RoHS, REACH</li> <li>- North America compliance: cETLus (3166456)</li> <li>- Safety standards: UL 507, CSA C22.2 № 113</li> </ul>
<b>Warranty period</b>	2 years / 40 000 motor hours

