



Image is for illustrative purposes only. Actual product may vary.

Nominal data

Model	BD-B225G-EC-00
Motor model	MEC3L-72-A0-00

Phase		
Nominal Voltage	VAC	
Nominal voltage range	VAC	
Frequency	Hz	

Speed	RPM	2400
Power consumption	W	85
Current draw	A	3.5
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	+60

Power and current values represent maximum ratings; speed values are specified at maximum efficiency point.

Data according to Commission Regulation (EU) 2024/1834

General parameters		
Measurement category		
Overall efficiency, ns	%	
Minimum efficiency, n	%	

Working point		
Power	W	
Flow rate	m ³ /h	
Pressure (Ps)	Pa	

Technical Data

Weight	1.25 kg
Impeller size	225 mm
Impeller material	PA plastic + 30% glass fiber
Number of blades	7
Direction of rotation	Clockwise, seen on rotor
Motor size	72
Bearing type	Ball bearings
Insulation class	B
Degree of protection	IP55
Motor protection	Self-resetting TOP wired internally
Operation mode	Continuous duty (S1)
Installation position	Any
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Cable length	500 ±20 mm
Technical features	<ul style="list-style-type: none">- Control Input 0-10 VDC / PWM- Locked Rotor Protection- Thermal Protection- Excessive Voltage Protection- Less Voltage Protection- Overcurrent Protection- Soft Start- Output 10 VDC, Max. 10 mA
Conformity with standards	<ul style="list-style-type: none">- Material compliance: RoHS, REACH- Quality certification: ISO 9001
Warranty period	2 years / 40 000 motor hours

