



Image is for illustrative purposes only. Actual product may vary.

### Nominal data

<b>Model</b>	<b>BL-B133B-EC-05</b>	
<b>Motor model</b>	<b>MEC3E-59-40-00</b>	

<b>Phase</b>		1~
<b>Nominal Voltage</b>	VAC	230
<b>Nominal voltage range</b>	VAC	
<b>Frequency</b>	Hz	50/60

<b>Speed</b>	RPM	3800
<b>Power consumption</b>	W	30
<b>Current draw</b>	A	0.38
<b>Min. ambient temperature</b>	°C	-25
<b>Max. ambient temperature</b>	°C	+60

Power and current values represent maximum ratings; speed values are specified at maximum efficiency point.

### Data according to Commission Regulation (EU) 2024/1834

General parameters		
<b>Measurement category</b>		
<b>Overall efficiency, ns</b>	%	
<b>Minimum efficiency, n</b>	%	

Working point		
<b>Power</b>	W	
<b>Flow rate</b>	m <sup>3</sup> /h	
<b>Pressure (Ps)</b>	Pa	

**Technical Data**

<b>Weight</b>	0.65 kg
<b>Impeller size</b>	133 mm
<b>Impeller material</b>	PA plastic + 30% glass fiber
<b>Number of blades</b>	7
<b>Direction of rotation</b>	Clockwise, seen on rotor
<b>Motor size</b>	59
<b>Bearing type</b>	Ball bearings
<b>Insulation class</b>	B
<b>Degree of protection</b>	IP55
<b>Motor protection</b>	Self-resetting TOP wired internally
<b>Operation mode</b>	Continuous duty (S1)
<b>Installation position</b>	Any
<b>Min. permitted ambient temp. for motor (transport/storage)</b>	-40 °C
<b>Max. permitted ambient temp. for motor (transport/storage)</b>	+80 °C
<b>Cable length</b>	500 ±20 mm
<b>Conformity with standards</b>	- Safety standards: EN 60335-1, EN 60335-2-80 - Material compliance: RoHS, REACH - Quality certification: ISO 9001
<b>Warranty period</b>	2 years / 40 000 motor hours

