



Image is for illustrative purposes only. Actual product may vary.

Nominal data

Model	BL-B190B-EC-02	
Motor model	MEC3E-72-95-00	

Phase		1~
Nominal Voltage	VAC	230
Nominal voltage range	VAC	
Frequency	Hz	50/60

Speed	RPM	2600
Power consumption	W	46
Current draw	A	0.4
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	+60

Power and current values represent maximum ratings; speed values are specified at maximum efficiency point.

Technical Data

Weight	1 kg
Impeller size	190 mm
Impeller material	PA plastic + 30% glass fiber
Number of blades	7
Direction of rotation	Clockwise, seen on rotor
Motor size	72
Bearing type	Ball bearings
Insulation class	B
Degree of protection	IP55
Motor protection	Self-resetting TOP wired internally
Operation mode	Continuous duty (S1)
Installation position	Any
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Cable length	500 ±20 mm
Technical features	<ul style="list-style-type: none"> - Output 10 VDC, Max. 10 mA - Control Input 0-10 VDC / PWM - Locked Rotor Protection - Thermal Protection - Excessive Voltage Protection - Less Voltage Protection - Overcurrent Protection - Soft Start
Conformity with standards	<ul style="list-style-type: none"> - Safety standards: EN 60335-1, EN 60335-2-80 - Electromagnetic compatibility: EN IEC 61000-3-2, EN 61000-3-3, EN IEC 61000-6-1, EN IEC 61000-6-3, EN IEC 55014-1, EN IEC 55014-2 - EU compliance: CE, RoHS, REACH - Quality certification: ISO 9001
Warranty period	2 years / 40 000 motor hours

